



STANDARD MODELS

- Frame 1** Line pull capacities to 2,000 lbs
Line speeds to 51 fpm
- Frame 2** Line pull capacities to 3,150 lbs
Line speeds to 45 fpm
- Frame 3** Line pull capacities to 5,000 lbs
Line speeds to 28 fpm

FEATURES

- Rated for hoisting loads vertically
- Dependable vane motor
- Totally enclosed watertight components
- Automatic, load suspending braking system
- Permanently lubed, 3-stage planetary geartrain
- Various motor horsepowers and input speeds available
- Simple installation at any angle

CUSTOM DESIGNS

Custom designs are available to meet your exact requirements for any lifting, pulling or positioning application with pneumatic, hydraulic, electric and self-contained power sources.

**More standard models.
More performance.
More options.
More value.**

OPTIONS

- Hoist mounted manual control valves
- Remote valve with pneumatic pendant
- Lagged, grooved and divided drums
- Cable tensioners
- Strap drum conversion
- AutoAdvance Line Spooler
- I-Beam trolleys, Hammerhead systems
- Quick-mount brackets
- Wire rope, sheaves, snatch blocks and other rigging

Distributed by:



1040 RUE ROBERT, ST-JÉRÔME, QC, J5L 2G9
TÉL : (450) 565-6141 / MTL : (450) 476-6065
FAX : (450) 565-3432 / EMAIL : info@reptech.ca
SITE WEB : www.reptech.ca